2000 ORDERING SUPPLEMENT
MIDDLE EAST

0smid82g

REQUIRED ALL MID-EAST ORDERS		
RPO	**DESCRIPTION**	
AC7	Fuel Tank Fill Pipe - Unrestricted	X
A04	Windshield: Tinted, less Upper Shadeband	X
EXP	Processing Option: GMODC, Export - Includes VZ2 Speedometer Calibration 170 kph Fuel Cut-off.	X
K47	Air Cleaner: High Capacity	X
K53	Fuel Sender Assembly, Robust Fuel System	X
NM2	Leaded Fuel Provisions	X
R6K	Processing Option – Middle East	X
T62	Daytime Running Lights - Delete	X
UC2	Speedometer: Kilo/Miles, Kilo Odometer, Positive Bias	X
UD4	Speed Warning Device	X
V87	Vehicle Certification Label: Complete Vehicle	X
VC5	Shipping Label	X
VPH	Export Vehicle Preparation – Includes (BAG) Export Parts Package, (VR6) Tie Down Hook (except with Z82), (V76) Front Tow Hooks	X
Z5X	Mirror: Outside, Rearview with Arabic Language Warning	X

MUST ORDER UL5 OR UL2		
UL5	Radio Delete – **Not Available** with YE9	A
UL0	Radio: Am/FM Stereo, Seek/Scan, Cassette, Clock ETR – **Requires** UL2. **Requires** YE9	A
UL2	Radio Frequency: Europe – **Requires** UL0, UM7 or UP0	A
UM7	Radio: AM/FM Stereo, Seek/Scan, Clock, ETR – **Requires** UL2; **Not Available** with YE9	A
UP0	Radio: AM/FM Stereo, Seek/Scan, Cassette, CD, Clock, ETR – **Requires** UL2, YE9 and MT1; **Not Available** with AE7	A

MODEL AND POWERTRAIN AVAILABILITY						
MODEL	**DESCRIPTION**	**ENG**	**DISPL.**	**TRANS.**	**AXLE**	**TIRES**
TC25903	2WD Regular Cab Long Box Pick-up with C6P	LQ4	6.0L V8	MT1/MW3	GT5	QIW/QIZ
TC25753	2WD Extended Cab Short Box Pick-up	LQ4	6.0L V8	MT1	GT5	QIW/QIZ
TK25903	4x4 Regular Cab Long Box Pick-up	LQ4	6.0L V8	MT1/MW3	GT5	QIW/QIZ
TK25753	4x4 Extended Cab Short Box Pick-up	LQ4	6.0L V8	MT1/MW3	GT5	QIW/QIZ
TK25953	4x4 Extended Cab Long Box Pick-up	LQ4	6.0L V8	MT1/MW3	GT5	QIW/QIZ

EXPORT RESTRICTIONS:	
AJ1	Glass: Deep Tint - **Not Available**
DF2	Mirrors, Exterior – **Not Available**
DL8	Mirrors, Exterior – **Not Available**

REGULAR CAB PICKUP

8 FOOT CARGO BOX 2 WHEEL DRIVE	C25903
8 FOOT CARGO BOX 4 WHEEL DRIVE	K25903

EXTENDED-CAB PICKUP

6.5 FOOT CARGO BOX 2 WHEEL DRIVE	C25753
6.5 FOOT CARGO BOX 4 WHEEL DRIVE	K25753
8 FOOT CARGO BOX 2 WHEEL DRIVE	C25953
8 FOOT CARGO BOX 4 WHEEL DRIVE	K25953

"STEP by STEP"

STEP #1:	SELECT	MODEL CODE Review Standard Equipment
STEP #2:	SELECT	PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE
STEP #3:	SELECT	POWER TEAM REQUIREMENTS
STEP #4:	SELECT	ADDITIONAL OPTIONS
STEP #5:	SELECT	COLOUR, TRIM AND PAINT APPLICATION CODE

2000 LIGHT DUTY TRUCKS

STEP #1: SELECT MODEL CODE – Review Standard Equipment

	SAFETY/SECURITY	ZE5	YE9
	Air Bag Restraint: Next Generation Driver and Passenger Sides. Passenger Side Air Bag suppression switch, located on instrument panel beneath the cargo lamp switch	S	S
	Child Safety Seat Top Tether Anchor	S	S
	Lights: Daytime Running Lights with automatic headlamp control; Centre high mounted stop lamp	S	S
	Passlock II ™Security System	S	S
	Side Guard Door Beams	S	S
	Single Two-Sided Key: Common key to operate ignition and doors	S	S
	EXTERIOR		
	Air Dam: Black (with C5Z only)	S	S
	Antilock Brakes: ABS 4 Wheel Disc	S	S
	Bumpers: Front, chrome with spectra gray cover	S	S
	Rear step painted argent (ZE5) Chrome with step pad (YE9)	S	S
R	**Door:** Fourth Door. Driver Side Rear Door (C/K25753, C/K25953)	S	S
	Door Sill Plates: Dark gray - ZE5; Colour-Keyed - YE9	S	S
	Easy Access System: Third Door (C/K25753, C/K25953)	S	S
	Glass: Solar-Ray™ tinted; all windows	S	S
	Grille: Moulded plastic; painted argent; integral GMC emblem at centre of grille	S	---
	Moulded plastic; painted argent; integral GMC emblem at centre of grille; chrome accents	---	S
	Headlamps: Automatic Dual Composite – Halogen	S	S
	Horn: Single, electric low note – ZE5; Dual, electric high/low note – YE9	S	S
	Insulators: Cab-to-fender; hood	---	S
	Keyless Entry, Remote: Three-button fob remote transmitter. Illuminated entry, panic alarm and vehicle content theft alarm. Two key fobs are provided	---	S
	Licence Plate Holder Front	S	S
	Lights: Backup lamps, Combination Parking/Direction/Hazard, Combination Tail/Stop/Direction/Hazard, Headlamps, License Plate lamp, Side Marker lamps with reflectors, Cargo lamp, Underhood lamp	S	S
	Mirrors: Black. Below eye-line type. Fold-away	S	S
	Electric Remote Control with chrome accents	---	S
	Mouldings: Black hidden roof drip mouldings	S	S
	Chrome body side	---	S
	Painted wheel opening flare mouldings (K25903, K25753, K25953)	S	S
	Nameplates: "SL"/"SLE"/"SLT" nameplate on B pillar. Series designation nameplate on doors	S	S
	"4 x 4" decals at rear of pickup box side panels (K models)	S	S
	"GMC" decal on tailgate	S	S
	"GMC" "Sierra" on lower tailgate	---	S
	Pickup Box: All steel double sidewall and tailgate construction, painted body colour	S	S
	Spare Tire Carrier: Lockable winch-type mounted under the frame in the rear	S	S
	Tow Hooks: Two, front mounted at the front of each frame side member	S	S
	Wheel Trim: Clad wheel silver painted steel with black centre cap	S	---
	Chrome Styled 16" x 6.5" with Chrome Centre Caps.	---	S
	Window: Swing-out rear quarter vent (C/K25753, C/K25953)	S	S
	Windshield Wipers and Washers: Intermittent wiper system. Demand-type washer system	S	S
	Wiring Harness, Trailer: 6-lead	S	S
	INTERIOR		
	Air Conditioning	---	S
	Convenience Group: Power locks, cruise control, power windows with express down feature on driver's window	---	S
	Defogger: Windshield and side window defoggers	S	S
	Door Trim Panels: Colour-keyed grained moulded plastic (ZE5); Soft vinyl with carpet covered map pocket and cloth insert (YE9)	S	S
	Floor Covering: black vinyl floor covering	S	---
	Colour-keyed carpeting and removable front vinyl mats	---	S
	Rear mats (C/K25753, C/K25953)	---	S
	Gauges: Speedometer, odometer, fuel level, voltmeter, temperature, oil pressure, tachometer, trip odometer, hour meter	S	S
	Headlamps-On and Key-In-Ignition Warning Buzzers	S	S
	Headliner: Full length colour-keyed cloth with matching retainer mouldings	S	S
	Insulator: Cab back panel	S	S
	Lights: Dome lamps, incorporating a 20 second delay-off feature. Map reading lights, underdash courtesy, ashtray and glove box. Left hand and right hand door jamb switches	S	S
	Mirror, Rearview: 254 mm (10") prismatic with soft vinyl rim	S	S
	Power Points: Dual Covered in addition to cigarette lighter receptacle in instrument panel	S	S
	Radio Equipment: Electronically Tuned AM/FM Stereo Digital Clock. Includes speakers in front doors. (C/K25903)	S	---
	Electronically Tuned AM/FM Stereo with Seek-Scan and Digital Clock. Includes fixed mast antenna and four speakers (2 - front doors; 2 - rear pillar) (C/K25753, C/K25953)	S	---
	ETR AM/FM Stereo with Compact Disc Player, SS, Auto Tone Control, Clock, Anti Theft Lock and Speed Control Volume. Includes six speakers (2 in door, 2 tweeter in armrest and 2 in rear pillar on regular cab or trim panel on extended cab)	---	S

S Standard

2000 LIGHT DUTY TRUCKS

STEP #1: SELECT MODEL CODE – Review Standard Equipment

INTERIOR	ZE5	YE9
Seats: Front Vinyl 40/20/40 Split Bench Seat	S	---
Front Custom Cloth reclining 40/20/40 Split Bench Seat with manual lumbar and center armrest storage	---	S
Rear folding seat (C/K25753, C/K25953)	S	S
Head restraints, adjustable on all outboard seats	S	S
Seat Belts: Seat mounted belts on front outboard seat	S	S
Steering Wheel and Column: Black energy absorbing, adjustable tilt steering wheel with anti-theft locking feature	S	S
Simulated leather sport wheel with four spokes	S	---
Leather wrapped sport wheel with four spokes	---	S
Sunshades: Left hand and right hand padded; colour-keyed cloth; left hand with storage strap; right hand with visor mirror	S	---
Left hand and right hand padded; colour-keyed cloth; left hand with storage strap; right hand with visor mirror	---	S
Tools: Mechanical jack and wheel wrench located in a storage compartment behind the seat	S	S
Transfer Case: Manual Two Speed (K25903, K25753, K25953)	S	S

S Standard

STEP #2: SELECT PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT

REFER TO GENERAL INFORMATION SECTION FOR HOW TO ORDER INFORMATION WHEN CHANGING POWERTRAIN

NOTE: SEE POWER TEAM CHARTS FOR CORRECT UPGRADES COMPATIBILITY

C25903, C25753 – 3266 KG (7200 LB) GVWR

		SELECT-A-UNIT CODES			
		SL		SLE	SLT
OPTION DESCRIPTION	OPTION CODE	1	2	3	C25753 4
PREFERRED EQUIPMENT GROUPS	---	1SA	1SB	1SC	♦1SD
MODEL OPTION: SL	ZE5	X	X		
BODY ORDERING CODE: Fleetside	E63	X	X	X	X
Engine: 5300 SFI V8	LM7	U	U	U	U
Transmission: 4 Speed Automatic	M30	U	U	U	U
GVWR: 3266 kg (7200 lb)	C5Z	X	X	X	X
Axle, Rear: 3.73 Ratio (C25903)	GT4	U	U	U	
Axle, Rear: 3.42 Ratio (C25753)	GU6	U	U	U	U
Chassis: Standard Suspension	Z83	U	U	U	U
Tires: LT225/75R -16D Blackwall ALS	QHP	U	U	U	U
Seat: 40/20/40 Split Front Bench	AE7	X	X	U	
Seat: Full Featured Front High Back Reclining Buckets with Leather Trim (Includes folding rear bench seat and front floor console)	AN3				U
Air Conditioning	C60		X	S	S
Bumper: Rear Chrome	VB3		U	S	S
Grille: Chrome	V22		X	S	S
Radio: ETR AM/FM with Compact Disc	UN0			U	
Radio: ETR AM/FM with Compact Disc and Cassette	UP0				U
Mouldings: Black Body Side	B85		X		
Wheel Trim: Chrome styled with chrome centre caps	PY2		U	S	
MODEL OPTION: SLE / SLT	YE9			X	X
Defogger: Rear Window	C49				X
Fog Lamps	T96				X
Mirrors, Exterior: Heated Remote Control Electric	DL8				U
Mirror, Rearview: Interior, Light Sensitive with compass, O/S Temp	DF5				X
Wheels: Aluminum. 4 wheels only	PY0				X

♦ **Requires Leather Trim Code 122, 672 or 922. Leather is on seating surfaces only**
X **Option Included in Select-A-Unit. DO NOT DELETE**
U **Option Included in Select-A-Unit and May Be Deleted if Substitute Option is Specified**
S **Standard**

2000 LIGHT DUTY TRUCKS

STEP #2: SELECT PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT

REFER TO GENERAL INFORMATION SECTION FOR HOW TO ORDER INFORMATION WHEN CHANGING POWERTRAIN

NOTE: SEE POWER TEAM CHARTS FOR CORRECT UPGRADES COMPATIBILITY

C/K25903, C/K25953, K25753 – 3901 KG (8600 LB) GVWR

OPTION DESCRIPTION	OPTION CODE	SELECT-A-UNIT CODES SL 5	SL 6	SLE 7	SLT K25753 C/K25953 8
PREFERRED EQUIPMENT GROUPS	---	1SE	1SF	1SG	♦1SH
MODEL OPTION: SL	ZE5	X	X		
BODY ORDERING CODE: Fleetside	E63	X	X	X	X
Engine: 6000 SFI V8	LQ4	X	X	X	X
Transmission: 5 Speed Manual with Overdrive	MW3	U	U	U	
Transmission: 4 Speed Automatic	MT1				X
GVWR: 3901 kg (8600 lb)	C6P	X	X	X	X
Axle, Rear: 3.73 Ratio	GT4	U	U	U	U
Chassis: Standard Suspension	Z83	U	U	U	U
Tires: LT245/75R -16E Blackwall ALS	QIZ	U	U	U	U
Seat: 40/20/40 Split Front Bench	AE7	X	X	U	
Seat: Full Featured Front High Back Reclining Buckets with Leather Trim (Includes folding rear bench seat and front floor console)	AN3				U
Air Conditioning	C60		X	S	S
Bumper: Rear Chrome	VB3		U	S	S
Grille: Chrome	V22		X	S	S
Radio: ETR AM/FM with Compact Disc	UN0			U	
Radio: ETR AM/FM with Compact Disc and Cassette	UP0				U
Mouldings: Black Body Side	B85		X		
Wheel Trim: Chrome styled with chrome centre caps	PY2		U	S	
MODEL OPTION: SLE / SLT	YE9			X	X
Defogger: Rear Window	C49				X
Fog Lamps	T96				X
Mirrors, Exterior: Heated Remote Control Electric	DL8				U
Mirror, Rearview: Interior, Light Sensitive with compass, O/S Temp	DF5				X
Transfer Case: Autotrac Electronic (K Models)	NP8				X
Wheels: Aluminum. 4 wheels only	PY0				X

♦ **Requires Leather Trim Code 122, 672 or 922. Leather is on seating surfaces only**
X **Option Included in Select-A-Unit. DO NOT DELETE**
U **Option Included in Select-A-Unit and May Be Deleted if Substitute Option is Specified**
S **Standard**

STEP #2: SELECT PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE

Description	Model Code	Model Option	Select-A-Unit Code	Option Code

REGULAR CAB LONGBOX PICKUP – 2 WHEEL DRIVE – With 3266 KG (7200 LB) GVWR

SL				
Model Price	**C25903**	**ZE5**	**1**	**1SA**
Preferred Equipment Group Price	C25903	ZE5	2	1SB
SLE				
Model Price	**C25903**	**YE9**	**3**	**1SC**

REGULAR CAB LONGBOX PICKUP – 2 WHEEL DRIVE – With 3901 KG (8600 LB) GVWR

SL				
Model Price	**C25903**	**ZE5**	**5**	**1SE**
Preferred Equipment Group Price	C25903	ZE5	6	1SF
SLE				
Model Price	**C25903**	**YE9**	**7**	**1SG**

REGULAR CAB LONGBOX PICKUP – 4 WHEEL DRIVE – With 3901 KG (8600 LB) GVWR

SL				
Model Price	**K25903**	**ZE5**	**5**	**1SE**
Preferred Equipment Group Price	K25903	ZE5	6	1SF
SLE				
Model Price	**K25903**	**YE9**	**7**	**1SG**

2000 LIGHT DUTY TRUCKS

STEP #2: SELECT PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE

Description	Model Code	Model Option	Select-A-Unit Code	Option Code

EXTENDED-CAB SHORTBOX PICKUP – 2 WHEEL DRIVE – WITH 3266 KG (7200 LB) GVWR

SL				
Model Price	**C25753**	**ZE5**	**1**	**1SA**
Preferred Equipment Group Price	C25753	ZE5	2	1SB
SLE				
Model Price	**C25753**	**YE9**	**3**	**1SC**
SLT				
Model Price	**C25753**	**YE9**	**4**	**1SD**

EXTENDED-CAB LONGBOX PICKUP – 2 WHEEL DRIVE – WITH 3901 KG (8600 LB) GVWR

SL				
Model Price	**C25953**	**ZE5**	**5**	**1SE**
Preferred Equipment Group Price	C25953	ZE5	6	1SF
SLE				
Model Price	**C25953**	**YE9**	**7**	**1SG**
SLT				
Model Price	**C25953**	**YE9**	**8**	**1SH**

EXTENDED-CAB SHORTBOX PICKUP – 4 WHEEL DRIVE – WITH 3901 KG (8600 LB) GVWR

SL				
Model Price	**K25753**	**ZE5**	**5**	**1SE**
Preferred Equipment Group Price	K25753	ZE5	6	1SF
SLE				
Model Price	**K25753**	**YE9**	**7**	**1SG**
SLT				
Model Price	**K25753**	**YE9**	**8**	**1SH**

EXTENDED-CAB LONGBOX PICKUP – 4 WHEEL DRIVE – WITH 3901 KG (8600 LB) GVWR

SL				
Model Price	**K25953**	**ZE5**	**5**	**1SE**
Preferred Equipment Group Price	K25953	ZE5	6	1SF
SLE				
Model Price	**K25953**	**YE9**	**7**	**1SG**
SLT				
Model Price	**K25953**	**YE9**	**8**	**1SH**

STEP #3: SELECT POWER TEAM REQUIREMENTS

Engine, Transmission, Axle Ratio and GVWR Code Must Be Specified

C25903

					GVWR Code kgs lbs	C5Z 3266 7200		C6P 3901 8600	
					Axle Ratio	3.73	4.10	3.73	4.10
Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type		Axle Ratio Codes			
LM7 V8	5.3 Litre 327 Cu. In.	SFI	285 @ 5200	M30 - Automatic with overdrive		GT4	GT5	---	---
LQ4 V8	6.0 Litre 366 Cu. In.	SFI	300 @ 4800	MW3 -5 Speed manual		---	---	GT4	GT5
				MT1 - 4 Speed automatic		^GT4	^GT5	GT4	GT5

C25753

					GVWR Code kgs lbs	C5Z 3266 7200		
					Axle Ratio	3.42	3.73	4.10
Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type		Axle Ratio Codes		
LM7 V8	5.3 Litre 327 Cu. In.	SFI	285 @ 5200	M30 - Automatic with overdrive		# GU6	GT4	---
LQ4 V8	6.0 Litre 366 Cu. In.	SFI	300 @ 4800	MT1 - 4 Speed automatic		---	^ GT4	^ GT5

C25953

					GVWR Code kgs lbs	C6P 3901 8600	
					Axle Ratio	3.73	4.10
Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type		Axle Ratio Codes	
LQ4 V8	6.0 Litre 366 Cu. In.	SFI	300 @ 4800	MW3 – 5 Speed Manual		GT4	GT5
				MT1 – 4 Speed automatic		GT4	GT5

**Not Available with G80**
^ **Requires Z82**

2000 LIGHT DUTY TRUCKS

STEP #3: SELECT POWER TEAM REQUIREMENTS

Engine, Transmission, Axle Ratio and GVWR Code Must Be Specified

K25903

					GVWR Code kgs lbs	C6P 3901 8600	
					Axle Ratio	3.73	4.10
Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type		Axle Ratio Codes	
LQ4	6.0 Litre	SFI	300 @	MW3 – 5 Speed Manual		GT4	GT5
V8	366 Cu. In.		4800	MT1 – 4 Speed Automatic		GT4	GT5

K25753

					GVWR Code kgs lbs	C6P 3901 8600	
					Axle Ratio	3.73	4.10
Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type		Axle Ratio Codes	
LQ4	6.0 Litre	SFI	300 @	MW3 – 5 Speed Manual		GT4	GT5
V8	366 Cu. In.		4800	MT1 – 4 Speed Automatic		GT4	GT5

K25953

					GVWR Code kgs lbs	C6P 3901 8600	
					Axle Ratio	3.73	4.10
Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type		Axle Ratio Codes	
LQ4	6.0 Litre	SFI	300 @	MW3 – 5 Speed Manual		GT4	GT5
V8	366 Cu. In.		4800	MT1 – 4 Speed Automatic		GT4	GT5

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code

ENGINES: Refer to Power Teams Charts for engine availability.

Vortec 5300 Sequential Fuel Injection (SFI) V8.
Optional with: ..... C25903, C25753 ..... LM7

Vortec 6000 Sequential Fuel Injection (SFI) V8. C5Z **Requires** Z82.
Optional with: ..... C25903, C25753 with C5Z LQ4
..... C6P LQ4

TRANSMISSIONS: Refer to Power Teams Charts for transmission availability.

5-Speed Manual with overdrive.
Optional with: ..... C/K25903, K25753, C/K25953 with C6P MW3

4-Speed Automatic with overdrive. 4L60E.
Optional with: ..... C25903, C25753 with C5Z M30

4-Speed Automatic with overdrive. 4L80E.
Optional with: ..... SAU 5, 6, 7 or 8 ..... MT1
..... C25903, C25753 with C5Z MT1

GVWR: Refer to Power Teams Charts for GVWR availability.

3266 kg (7200 lb)
Optional with: ..... C25903, C25753 ..... C5Z

3901 kg (8600 lb).
Optional with: ..... C/K25903, K25753, C/K25953 ..... C6P

AXLES, REAR: Refer to Power Teams Charts for axle ratio availability.

3.42 Ratio.
Optional with: GU6

3.73 Ratio
Optional with: GT4

4.10 Ratio
Optional with: GT5

Locking Differential G80

CHASSIS EQUIPMENT:

C25903, C25753, C25953
Standard Suspension. Twintube 32 mm shocks.
Requires C5Z and QHP or QIZ on C25903 and C25753
Requires C6P and QIW or QIZ on C25903 and C25953
Optional with: Z83

Heavy Duty: Monotube 36 mm shocks. Provides increased damping to improve handling or trailering.
Requires C5Z or C6P and QIW or QIZ
Optional with: Z85

K25903, K25753, K25953
Standard Suspension. Twintube 32 mm shocks.
Requires QIW or QIZ
Optional with: Z83

Heavy Duty: Monotube 36 mm shocks. Provides increased damping to improve handling or trailering.
Requires QIW or QIZ
Optional with: Z85

TIRES: (Includes front, rear and spare)

LT225/75R-16D – Blackwall Radial Steel All Seasons
Requires C5Z and Z83.
Optional with: ..... C25903, C25753 ..... QHP

LT245/75R-16E – Blackwall Radial Steel On/Off Road
Requires C5Z and Z85 on C25903, C25753.
Requires C6P and Z83 or Z85 on C25903, C25953.
Optional with: ..... C25903, C25753 with C5Z ..... QIW
..... C25903, C25953 with C6P ..... QIW

LT245/75R-16E – Blackwall Radial Steel All Seasons
Requires C5Z and Z83 or Z85 on C25903, C25753.
Requires C6P and Z83 or Z85 on C25903, C25953.
Optional with: ..... C25903, C25753 with C5Z ..... QIZ
..... C25903, C25953 with C6P ..... QIZ

2000 LIGHT DUTY TRUCKS

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code

LT245/75R-16E – Blackwall Radial Steel On/Off Road
Requires Z83 or Z85.
Optional with: ..... K25903, K25753, K25953 ..... QIW

LT245/75R-16E – Blackwall Radial Steel All Seasons
Requires Z83 or Z85.
Optional with: ..... K25903, K25753, K25953 ..... QIZ

SEATS AND SEAT TRIM: Cloth trim.

C/K25903

ZE5 includes driver manual seat back recliner, fixed centre bench without armrest.
YE9 includes driver and passenger manual seat back recliner, manual driver and passenger lumbar, folding center bench that will function as armrest with stowage provisions and mini roof console.
Optional with: ..... 'V' Trim..... SAU 1, 2, 5 or 6 ..... AE7
..... 'C' Trim..... SAU 1, 2, 5 or 6 ..... AE7
..... 'D' Trim..... SAU 3 or 7 ..... AE7

High back bucket seat with manual recliners and adjustable head restraint. Inboard arm rest on driver and passenger. Manual lumbar on driver and passenger. Includes mini overhead console and floor console.
Optional with: ..... 'D' Trim..... SAU 3 or 7 ..... A95

C/K25753, C/K25953

40/20/40 Split Front Bench.
ZE5 includes driver manual seat back recliner, fixed centre bench without armrest.
YE9 includes driver and passenger manual seat back recliner, manual driver and passenger lumbar, seat back stowage pockets, folding center bench that will function as armrest with stowage provisions and mini roof console.
With '2' Leather trim includes driver and passenger power 6-way seat adjuster.
Optional with: ..... 'V' Trim..... SAU 1, 2, 5 or 6 ..... AE7
..... 'C' Trim..... SAU 1, 2, 5 or 6 ..... AE7
..... 'D' Trim..... SAU 3 or 7 ..... AE7
..... '2' Leather Trim..... SAU 4 or 8 ..... AE7

High back bucket seat with manual recliners and adjustable head restraint. Inboard arm rest on driver and passenger. Manual lumbar on driver and passenger. Seat back stowage pockets. Includes full length overhead console and floor console.
With '2' Leather trim includes driver and passenger power 6-way seat adjuster.
Optional with: ..... 'D' Trim..... SAU 3 or 7 ..... A95
..... '2' Leather Trim..... SAU 4 or 8 ..... A95

Full feature high back bucket seat with driver and passenger power 6-way seat adjuster. Inboard arm rest on driver and passenger. Power lumbar, seat back bolster, seat back recliners, and seat back stowage pockets. Two position memory controls. Heated seat for driver and passenger. Includes full length overhead console and floor console.
Optional with: ..... '2' Leather Trim..... SAU 4 or 8 ..... AN3

AIR CLEANER: High Capacity. Included with LQ4.
Optional with: ..... C25903, C25753 ..... K47

AIR CONDITIONING: All Weather. Included with YE9. Includes Increased Capacity Cooling.
Optional with: ..... SAU 1 or 5 ..... C60

BATTERY: Additional 600 CCA Battery. **Requires** LM7 or LQ4.
Optional with: TP2

BUMPER EQUIPMENT:

Bumper, Chrome, Rear Step
Optional with: ..... SAU 1 or 5 ..... VB3

Bumper, Painted Rear Step
Included with E63 and SAU 1 and 5 unless VB3 or VF7 is specified. **Requires** E63.
Optional with: ..... SAU 2 or 6 ..... V43

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code

Bumper Delete, Rear Step. **Not Available** with Z82.
Deletes standard rear step bumper.
Optional with: VF7

CONVENIENCE GROUPS:
Power Door Locks. Included with YE9. Includes Lockout protection.
Optional with: ..... SAU 1, 2, 5 or 6 ..... AU3

Cruise Control. Included with YE9.
Optional with: ..... SAU 1, 2, 5 or 6 ..... K34

Driver and Passenger 6-Way Power Seat Adjuster. Included with "2' Leather Trim.
Requires AE7 or A95 and 'D' Code Trim.
Optional with: ..... SAU 3, 4, 7 or 8 ..... AG2

COOLING SYSTEMS: Extra capacity.
Engine Oil. Available with LQ4.
Includes an external engine oil cooler
Optional with: KC4

Transmission Oil Cooler. Provides an external air-to-oil cooling system. **Requires** M30.
Included with MT1.
Optional with: ..... KNP

DEFOGGER, REAR WINDOW: Electric. **Not Available** with A28. **Requires** C60 on ZE5.
Optional with: ..... SAU 1, 2, 3, 5, 6 or 7 ..... C49

FLOOR COVERING:
Carpet, Colour-Keyed with colour -keyed vinyl front floor mats.
Includes rear mats on C/K25753 and C/K25953.
Optional with: ..... SAU 1, 2, 5 or 6 ..... B30

Vinyl front removeable floor mats. **Requires** B30.
Optional with: ..... SAU 1, 2, 5 or 6 ..... B32

Rear vinyl front removeable floor mats. **Requires** B30 and B32.
Optional with: ..... SAU 1, 2, 5 or 6 on C/K25753, C/K25953 ..... B33

Vinyl, Colour-Keyed. Replaces carpet. **Deletes** floor mats.
Requires 12D, 122, 67D or 672 Trim.
Optional with: ..... SAU 3 or 7 on C/K25903 ..... BG9
..... SAU 3, 4, 7 or 8 on C/K25753, C/K25953 ..... BG9

FOG LAMP:
Optional with: ..... SAU 1, 2, 3 5, 6 or 7 ..... T96

GLASS: Deep Tinted Glass on Quarter and Rear Window. Light Tinted Glass on all other windows.
C/K25903 **Requires A28 or C49.**
Optional with: AJ1

GRILLE: Chrome accents. Includes dual horns.
Optional with: ..... SAU 1 or 5 ..... V22

HEATER: Engine Block.
Optional with: K05

MIRRORS, EXTERIOR:
Left Hand and Right Hand. Camper Type. Incorporates ability to be extended outboard to give greater field of view for trailering applications and after market body equipment.
Optional with: DF2

Left Hand and Right Hand, Remote Control, Electric, Heated
Requires C49.
Optional with: ..... SAU 3 or 7 ..... DL8

MIRROR, REARVIEW: Interior. 254 mm (10") Light Sensitive. Includes a mirror that automatically adjusts to reduce night time glare and a continually recalibrating 8 point compass system and outside temperature.
Optional with: ..... SAU 3 or 7 ..... DF5

2000 LIGHT DUTY TRUCKS

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code

MOULDINGS: Black Body Side.
Optional with: ..... SAU 1 or 5 ..... B85

PAINT SCHEMES: (Refer to Colour, Trim and Seat Availability Chart)
Solid ZY1
Conventional Two-Tone.
Optional with: ..... SAU 3, 4, 7 or 8 ..... ZY2

RADIO EQUIPMENT:
Radio Delete (**Deletes** radio, antenna and speakers)
Optional with: ..... SAU 1, 2, 5 or 6 ..... UL5

Electronically Tuned AM/FM Stereo with Cassette Player, Seek-Scan, Automatic Tone Control, Clock, Anti Theftlock and Speed Control. Includes six speakers (two high sensitivity speakers in front doors, two tweeters in front door armrests and two speakers in rear pillar in regular cab or two speakers in quarter trim panel and rear side door in extended cab).
Optional with: ..... SAU 3 or 7 ..... UL0

Electronically Tuned AM/FM Stereo Radio with Seek-Scan, Cassette Player and Digital Clock. Includes four speakers (two in front doors, two in rear pillar).
Optional with: ..... C/K25903 on SAU 1, 2, 5 or 6 ..... UM6
..... C/K25753, C/K25953 on SAU 1, 2, 5 or 6 ..... UM6

Electronically Tuned AM/FM Stereo with Compact Disc Player, Seek-Scan, Automatic Tone Control, Clock, Anti Theftlock and Speed Control. Includes six speakers (two high sensitivity speakers in front doors, two tweeters in front door armrests and two speakers in rear pillar in regular cab or two speakers in quarter trim panel and rear side door in extended cab).
Optional with: ..... SAU 4 or 8 ..... UN0

Electronically Tuned AM/FM Stereo with Cassette Player and Compact Disc Player, Seek-Scan, Automatic Tone Control, Clock, Anti Theftlock and Speed Control. Includes six speakers (two high sensitivity speakers in front doors, two tweeters in front door armrests, two speakers in rear pillar). **Requires** MT1 or M30 and AN3 or A95 with C25753 or C25953. **Requires** NP8 and AN3 or A95 with K25753 or K25953.
Optional with: ..... SAU 3 or 7 on C/K25753, C/K25953 ..... UP0

SKID PLATES: Off-Road. Includes shields for engine, transmission, front differential and transfer case.
Optional with: ..... K25903, K25753, K25953 ..... NZZ

SPEEDOMETER: Kilo/Miles, Kilo Odometer. **Not Available** with CU7 (Kuwait), CU8 (Saudi Arabia), CW2 (Gulf States), CW6 (Guam) or (CW7 (Caribbean)
Optional with: U19

TELEPHONE PROVISIONS: Includes wiring for remote control and cellular phone.
Optional with: UV8

TONNEAU COVER: Pick Up Box.
Soft cover design, box rails are plant installed, cover and bows are shipped in cab and dealer installed.
Optional with: E95

TRAILERING SPECIAL EQUIPMENT: Heavy Duty. Includes weight distributing platform trailer hitch. Includes heavy duty 8 – lead wiring harness with 7 – way sealed connector. **Includes** KC4 on LQ4. Includes KNP Extra Capacity Transmission cooling on M30 and MT1. Includes Automatic Transmission Temperature Gauge with LQ4 and MT1.
Optional with: Z82

TRANSFER CASE: Autotrac. **Requires** MT1.
Automatic Four Wheel Drive function in addition to the traditional 2H/4H/4L. Switch, located in the lower section of the instrument panel, to the left of the steering column.
Optional with: ..... SAU 3 or 7 on K25903, K25753, K25953 ..... NP8

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code

WHEELS:
Aluminum. Four Wheels. Wheel size is 406 mm x 165 mm (16" x 6.5").
Optional with: ..... SAU 1, 2, 3, 5, 6 or 7 ..... PY0

Chrome. Four Wheels only. Wheel size is 406 mm x 165 mm (16" x 6.5"). Includes Chrome Caps. Included on YE9.
Optional with: ..... SAU 1 or 5 ..... PY2

Chrome Caps.
Optional with: ..... SAU 1 or 5 ..... P03

WINDOW: Sliding Rear. **Not Available** with C49. **Deletes** C49 and DL8 on SAU 4 or 8.
Optional with: A28

WIRING PROVISIONS: Camper and 5th Wheel Trailer. Includes 8 wire independently fused wiring harness routed to the front of the pickup box. Includes an additional 7 way sealed connector. **Requires** Z82 and LM7 or LQ4.
Optional with: UY2

DESCRIPTION	Order Code		Lead Time Days

SPECIAL EQUIPMENT WHEN INSTALLED AT ASSEMBLY PLANT

CONSOLE DELETE: Deletes Floor Console.
Requires A95 on C/K25903.
Requires AN3 or A95 and UL0 or UN0 on C/K25753, C/K25953.

Optional with:	SAU 3 on C25903	9N5	49
	SAU 7 on C/K25903	9N5	49
	SAU 3 or 4 on C25753	9N5	49
	SAU 7 or 8 on K25753, C/K25953	9N5	49

PAINTS: Solid. **Requires** 01U. Wheel flare mouldings on K25903, K25753, K25953 are black.

Green, Woodland	9V5	42
Tan, Doeskin	9V9	42
Yellow, Wheatland	9W3	42
Orange, Tangier	9W4	42

SEAT, REAR. DELETION: Requires 9X5 with the combination of ZE5 and A95.
Requires YE9 with AE7. With YE9 **Deletes** rear mats.

Optional with:	C/K25753, C/K25953	8Q3	49

TRIM OVERRIDE: Provides custom cloth seats. **Requires** ZE5 and 12C or 67C code trim.
Requires AE7 or A95.
AE7 includes manual lumbar and center storage armrest.
A95 includes manual lumbar on driver and passenger. Does not include overhead console or floor console.

Optional with:	SAU 1 , 2, 5 or 6 on C/K25903	9X5	49
	SAU 1 or 2 with 8Q3 on C25753	9X5	49
	SAU 1 or 2 without 8Q3 on C25753	9X5	49
	SAU 5 or 6 with 8Q3 on K25753, C/K25953	9X5	49
	SAU 5 or 6 without 8Q3 on K25753, C/K25953	9X5	49

SEATS, FRONT: Requires 9X5.
Split Bench.

Optional with:	SAU 1, 2, 5 or 6	AE7	- -

High Back Reclining Buckets.

Optional with:	SAU 1, 2, 5 or 6 on C/K25903	A95	- -
	SAU 1 or 2, on C25753	A95	- -
	SAU 5 or 6 on K25753, C/K25953	A95	- -

2000 LIGHT DUTY TRUCKS

STEP #5: SELECT COLOUR, TRIM AND PAINT APPLICATION CODE

ZY1 PAINT APPLICATION

Model Option	Seat Ordering Information			Interior Trim		
	Type	Seat Material	Option Code	Graphite	Med Oak	Med Gray
ZE5	40/20/40 Split Bench	Vinyl	AE7	12V	67V	---
	40/20/40 Split Bench	Cloth	AE7	12C	67C	---
YE9	40/20/40 Split Bench	Custom Cloth	AE7	12D	67D	92D
	40/20/40 Split Bench	Leather	AE7	♦122	♦672	♦922
	High Back Bucket	Custom Cloth	A95	12D	67D	92D
	High Back Bucket	Leather	A95	♦122	♦672	♦922
	High Back Bucket	Leather	AN3	♦122	♦672	♦922

Exterior Paint Colour	Code	Available Combinations			^Wheel Opening Fender Flares	
					with ZE5	with YE9
Pewter (Met)	11U	X	X	X	Black	Pewter
Storm Gray (Met)	14U	X	X	X	Black	Gray
Indigo Blue (Met)	39U	X	X	X	Black	Black
Black Onyx	41U	X	X	X	Black	Black
Summit White	50U	X	X	X	Black	Black
Dark Toreador Red (Met)	#51U	X	X	X	Black	Black
Sunset Gold (Met)	#60U	X	X	X	Black	Gold
R Meadow Green (Met)	68U	X	X	X	Black	Green
Fire Red	74U	X	X	X	Black	Black

 # Not Available With ZE5
^ Wheel Flares Standard on K25903, K25753 and K25953
♦ Leather Trim Requires SAU 4 or 8 and Automatic Transmission. Leather is on seating surfaces only

STEP #5: SELECT COLOUR, TRIM AND PAINT APPLICATION CODE

ZY2 PAINT APPLICATION

Model Option	Seat Ordering Information			Interior Trim		
	Type	Seat Material	Option Code	Graphite	Med Oak	Med Gray
YE9	40/20/40 Split Bench	Custom Cloth	AE7	12D	67D	92D
	40/20/40 Split Bench	Leather	AE7	♦122	♦672	♦922
	High Back Bucket	Custom Cloth	A95	12D	67D	92D
	High Back Bucket	Leather	A95	♦122	♦672	♦922
	High Back Bucket	Leather	AN3	♦122	♦672	♦922

Exterior Paint Colour	Code	Exterior Paint Colour	Code	Available Combinations			^Wheel Opening Fender Flare
Pewter (Met)	11U	Storm Gray (Met)	14L	X	---	X	Gray
Storm Gray (Met)	14U	Pewter (Met)	11L	X	---	X	Pewter
Indigo Blue (Met)	39U	Pewter (Met)	11L	X	---	X	Pewter
		Storm Gray (Met)	14L	X	---	X	Gray
Black Onyx	41U	Pewter (Met)	11L	X	---	X	Pewter
		Storm Gray (Met)	14L	X	---	X	Gray
Summit White	50U	Pewter (Met)	11L	X	---	X	Pewter
		Storm Gray (Met)	14L	X	---	X	Gray
Dark Toreador Red (Met)	51U	Pewter (Met)	11L	X	---	X	Pewter
		Storm Gray (Met)	14L	X	---	X	Gray
Sunset Gold (Met)	60U	Pewter (Met)	11L	---	X	X	Pewter
		Storm Gray (Met)	14L	X	X	---	Gray
Meadow Green (Met)	68U	Pewter (Met)	11L	X	---	X	Pewter
		Storm Gray (Met)	14L	X	---	X	Gray
Fire Red	74U	Pewter (Met)	11L	X	---	X	Pewter
		Storm Gray (Met)	14L	X	---	X	Gray

^ **Wheel Flares Standard on K25903, K25753 and K25953**

♦ **Leather Trim Requires SAU 4 or 8 and Automatic Transmission. Leather is on seating surfaces only**

DATE: February 14, 2000
REVISION NO: 00-3

GENERAL MOTORS OVERSEAS DISTRIBUTION CORPORATION

2000

UPDATE

GMC

SIERRA 2500 (NEW)

TRUCK TECHNICAL PAGES

Attached is revision 00-3 of the Light Duty Truck Technical Pages.

The information contained in the Technical Pages is confidential and should not be disclosed to unauthorized persons or used for non-business purposes.

MODEL SELECTION SUMMARY

SERIES	MODEL NUMBER/ BODY CODE	PASSENGER CAPACITY (STD./OPT.)	STANDARD ENGINE/ TRANS.	OPTIONAL ENGINE/ TRANS.	GVWR KG (LB)	GAWR KG (LB) FRONT/ REAR	BASE PAYLOAD KG (LB)	MAX GROSS TRAILER WT/ TONGUE LOAD KG (LBS)
TWO-WHEEL-DRIVE MODELS								
SIERRA 2500 REGULAR-CAB								
WIDESIDE LONG-BOX	TC25903/E63	3/2	5300 V8/A4	6000 V8/A4	3265 (7200)	1429/2118 (3150/4670)	1165 (2569)	4990/* (11000)
WIDESIDE LONG-BOX	TC25903/E63	3/2	6000 V8/M5	6000 V8/A4	3901 (8600)	1633/2722 (3600/6000)	1682 (3709)	4990/* (11000)
SIERRA 2500 EXTENDED-CAB								
WIDESIDE SHORT-BOX	TC25753/E63	6/5/3/2	5300 V8/A4	6000 V8/A4	3265 (7200)	1633/2118 (3600/4670)	1129 (2489)	4990/* (11000)
WIDESIDE LONG-BOX	TC25953/E63	6/5/3/2	6000 V8/M5	6000 V8/A4	3901 (8600)	1633/2722 (3600/6000)	1572 (3466)	4990/* (11000)
FOUR-WHEEL-DRIVE MODELS								
SIERRA 2500 REGULAR-CAB								
WIDESIDE LONG-BOX	TK25903/E63	3/2	6000 V8/M5	6000 V8/A4	3901 (8600)	2041/2722 (4500/6000)	1495 (3297)	4763/* (10500)
SIERRA 2500 EXTENDED-CAB								
WIDESIDE SHORT-BOX	TK25753/E63	6/5/3/2	6000 V8/M5	6000 V8/A4	3901 (8600)	2041/2722 (4500/6000)	1461 (3221)	4763/* (10500)
WIDESIDE LONG-BOX	TK25953/E63	6/5/3/2	6000 V8/M5	6000 V8/A4	3901 (8600)	2041/2722 (4500/6000)	1409 (3107)	4763/* (10500)

*Trailer tongue weight should be 10 to 15% of total loaded trailer weight (up to 1500 lbs).

POWERTRAINS

ENGINES		
ENGINE	**VORTEC 5300 V8**	**VORTEC 6000 V8**
Order Code	LM7 (Standard w/C5Z)	LQ4
SAE Net Kilowatts @ rpm (Horsepower @ rpm)	 213 @ 5200 (285 @ 5200)	 224 @ 4800 (300 @ 4800)
SAE Net Torque N-m @ rpm (lb-ft @ rpm)	 441 @ 4000 (325 @ 4000)	 481 @ 4000 (355 @ 4000)
Fuel System	SFI	SFI
Hydraulic Clutch Control Clutch Size mm (in.)	 279 (11)	 305 (12)
Standard Battery (12-volt negative ground Delco Freedom 2 Plus) Cold Cranking Amps @ -17.8° C (0° F)	 600	 600
Standard Delcotron Alternator Maximum Capacity Amps	 105	 105

TRANSMISSIONS			
	MANUAL	**AUTOMATIC**	**AUTOMATIC**
TRANSMISSIONS	**5-SPEED MANUAL W/OVERDRIVE AND DEEP LOW HEAVY-DUTY**	**ELECTRONICALLY CONTROLLED AUTOMATIC 4-SPEED W/OVERDRIVE (4L60-E)**	**ELECTRONICALLY CONTROLLED AUTOMATIC 4-SPEED W/OVERDRIVE HEAVY-DUTY (4L80-E)**
Transmission Order Code	MW3	M30	MT1
Synchronized Speeds	 1/2/3/4/5	 —	 —
Gear Ratio First Second Third Fourth Fifth Reverse	 5.61 3.04 1.67 1.00 0.75 5.61	 3.06 1.63 1.00 0.70 – 2.29	 2.48 1.48 1.00 0.75 – 2.08
Power Take-Off	Yes	No	No

POWERTRAINS (cont'd)

FRONT AXLE

Availability	K2500		
Make/Capacity kg (lb)	American Axle / 4800		
Pinion and Ring Gear Type	Hypoid		
Ratio	3.42	3.73	4.10
Pinion Teeth	12	11	10
Ring Gear Teeth	41	41	41
Ring Gear Diameter mm (in.)	235 (9.25)	235 (9.25)	235 (9.25)

REAR AXLES

Make	American Axle			American Axle		
Application kg (lb)	3266 (7200) GVWR			3901 (8600) GVWR		
Capacity kg (lb)	4800			6000		
Type	Semi-Floating			Semi-Floating		
Pinion and Ring Gear Type	Hypoid			Hypoid		
Axle Ratio Code	GU6 (Standard)	GT4	GT5	GU6	GT4	GT5
Ratio	3.42	3.73	4.10	3.42	3.73	4.10
Pinion Teeth	12	11	10	12	11	10
Ring Gear Teeth	41	41	41	41	41	41
Ring Gear Diameter mm (in.)	241[1] (9.5)	241[1] (9.5)	241[1] (9.5)	241[1] (9.5)	241[1] (9.5)	241[1] (9.5)

[1]268mm (10.5 inch) ring gear with full floating axle.

BRAKES

Type	Power 4-Wheel Anti-Lock
Application kg (lb)	2767-2903 (7200-8600) GVWR
Front Rotor Size mm (in.)	Disc 325 x 38 (12.79 x 1.49)
Rear Size mm (in.)	Disc[1] 330 x 29 (12.99 x 1.14)
Booster Type	Vacuum/Hydraulic
Parking Brake Type Operation	Cable to Rear Wheels Drum-in-hat/Pedal

[1] Rear axles with a 268mm(10.5 inch) ring gear diameter have a rear disc brake size of 330mm x 39mm(12.99in x 1.53in).

STANDARD CHASSIS FEATURES

ENGINE BLOCK HEATER	
EXHAUST SYSTEM	
Type	Aluminized stainless steel single exhaust with converter and unitized muffler tailpipe
FRAME	
Type	All-welded hydro formed ladder-type with channel design and boxed front section
Material	Carbon steel
Yield Strength	N/A
FUEL TANK	
Location	Forward of rear axle between frame rail and propshaft Includes plastic bathtub-type shield
Fuel Filter	Located in fuel feed line
Capacity (approx.)	
C/K 25753	98.4 litres (21.6 imperial gal)
C/K 25903/25953	128.7 litres (28.3 imperial gal)
GVWR	
C5Z-CC25903/CC25753	2767 kg (7200-lb)
C6P-CK25753/CK25903/ CK25953	2812 kg (8600-lb)
STEERING	
Type	Integral Power

SUSPENSION, FRONT	Independent
Capacity (C5Z)	
C25903 w/L30/L31	1542 kg (3400 lbs)
C25753	1633 kg (3600lbs)
Capacity (C6P)	
C25903	1724 kg (3800 lbs)
C25753/C25953	1633 kg (3600 lbs)
4WD models	1928 kg (4250 lbs)
2WD Springs	Coil
Capacity (C5Z)	
C25903	1429 kg (3150 lbs)
C25753	1429 kg (3150 lbs)
Capacity (C6P)	
C25903/C25753/C25953	1633 kg (3600lbs)
4WD springs	Torsion bars
Capacity	1928 kg (4250 lbs)
Shock absorbers	35mm (1.38") piston diameter
Stabilizer bar	Heavy-duty
SUSPENSION, REAR	
Springs	Two-stage multi-leaf
Capacity (C5Z)	2118 kg (4670 lbs)
Capacity (C6P)	2760 kg (6084 lbs)
Shock absorbers	35mm (1.38") piston diameter
TRANSFER CASE	
Availability	K25903/K25753/K25953
Type/Model	Part-time/New process 241
Controls	Floor mounted
WHEELS	
Type	Five disc
Size	406mm x 165mm (16" x 6.5")
Attachment	8 bolts on 165mm (6.5") circle

TIRES

KEY: AS = ALL-SEASON SBR = STEEL-BELTED RADIAL PLY BW = BLACKWALL WW = WHITEWALL WL = WHITE LETTERED HWY = HIGHWAY BL = BLACK LETTERED ON-OFF = ON-OFF ROAD WOL = WHITE OUTLINE LETTERED

TIRE DESCRIPTION		FRONT/REAR/SPARE
LT225/75R16D	AS/SBR/BW	QHP (Standard with C5Z)
LT245/75R16E	AS/SBR/BW	QIZ
LT245/75R16E	ON-OFF/SBR/BW	QIW

DIMENSIONS

MODEL	SIERRA 2500 PICKUP REG.-CAB/EXT.-CAB WIDESIDE		
MODEL NUMBER	CC25903/CC25753/C/K25753		C/K25903/ C/K25953
BODY CODE	C5Z	C6P	C6P
EXTERIOR DIMENSIONS			
BODY			
Wheelbase mm (in.)			
Regular Cab	3378 (133.0)		3378 (133.0)
Extended Cab	3645 (143.5)		4001 (157.5)
Overall Length mm (in.) w/o Rear Bumper			
Regular Cab	5639 (222.0)		5639 (222.0)
Extended Cab	5781 (227.6)		6261 (246.5)
Overall Height mm (in.)			
Regular Cab-2WD	1872 (73.7)		1803 (71.0)
Regular Cab-4WD	—		1872 (73.7)
Extended Cab-2WD	1880 (74.0)		1798 (70.8)
Extended Cab-4WD	1890 (74.4)		1872 (73.7)
Maximum Width mm (in.)	1994 (78.5)		5550 (78.5)
Bumper to Axle mm (in.)			
Front	940 (37.0)		940 (37.0)
Rear Overhang (w/o bumper)	1194 (47.0)		1321 (52.0)
Cab to Rear Axle mm (in.)	1064 (41.9)	1420 (55.9)	1420 (55.9)
Cab to End of Frame mm (in.)	1999 (78.7)	2479 (97.6)	2479 (97.6)
Bumper to Back of Cab mm (in.)			
Regular Cab	2901 (114.2)		2901 (114.2)
Extended Cab	3523 (138.7)		3523 (138.7)
Ground to Top of Rear Load Floor mm (in.)			
Regular Cab-2WD	889 (35.0)		889 (35.0)
Regular Cab-4WD	—		894 (35.2)
Extended Cab-2WD	866 (34.1)		876 (34.5)
Extended Cab-4WD	879 (34.6)		897(35.3)
Ground Clearance mm (in.) Front/Rear			
Regular Cab-2WD	201/190 (7.9/7.5)		201/190 (7.9/7.5)
Regular Cab-4WD	—		226/210 (8.9/8.3)
Extended Cab-2WD	201/188 (7.9/7.4)		201/206 (7.9/8.1)
Extended Cab-4WD	226/210 (8.9/8.3)		226/210 (8.9/8.3)
Turning Diameter Curb -to-Curb m (ft)			
Regular Cab-2WD/4WD	13.8/— (45.3/—)		13.8/13.7 (45.3/45.2)
Extended Cab-2WD/4WD	14.7/14.8 (48.2/48.4)		15.8/15.9 (52.1/52.3)
CARGO BOX			
Inside Length @ Floor mm (in.)	2001 (78.8)	2479 (97.6)	2479 (97.6)
Inside Width @ Top Rear mm (in.)	1529 (60.2)		1529 (60.2)
Inside Width @ Floor mm (in.)	1529 (60.2)		1636 (64.4)
Inside Width Between Wheelhousings mm (in.)	1270 (50.0)		1270 (50.0)
Inside Height mm (in.)	495 (19.5)		495 (19.5)
Tailgate Width Top mm (in.)	1539 (60.6)		1539 (60.6)
Cargo Volume litres (cu ft)	1611 (56.9)		2002 (70.7)

N/A–Not available at time of publication.

DIMENSIONS (cont'd)

MODEL	SIERRA 2500 PICKUP REG.-CAB/EXT.-CAB WIDESIDE		
MODEL NUMBER	CC25903/ CC25753/ C/K25753		C/K25903/C/K25953
BODY CODE	C5Z	C6P	C6P
INTERIOR DIMENSIONS			
CAB Headroom mm (in.) Front/Rear	1062/975 (41.8/38.4)		1062/975 (41.8/38.4)
Legroom mm (in.) Front/Rear	1049/856 (41.3/33.7)		1049/856 (41.3/33.7)
Shoulder Room mm (in.) Front/Rear[1]	1656/1684 (65.2/66.3)		1656/1684 (65.2/66.3)
Hip Room mm (in.) Front/Rear	1559/1562 (61.4/61.5)		1559/1562 (61.4/61.5)
Extended Cab Cargo Volume litres (cu ft) w/ Rear Seat Front/Rear	1826/1407 (64.5/49.7)		1826/1407 (64.5/49.7)